

यशवंतराव चव्हाण महाराष्ट्र मुक्त विद्यापीठ

ज्ञानगंगोत्री, गंगापूर धरणाजवळ, गोवर्धन, नाशिक- 422 222. दरथ्वनी (0253) 2230072 (कार्यो) 2231714/15, 2230227, 2234718

[Visit us on at www.ycmou.ac.in & http://ycmou.digitaluniversity.ac]

fl,																															
	-	,	-	~	-	-					-	-	~	-	-	-	-	-	-	-	-	-	 -	-	-	-	-	-	-	-	
		-			-	-	-	-	-	_	-			-	-	-							 								

जावक क्र.: UWD/ 2020-21/ 124 दिनांक : 23/10/2020

विषयः विद्यापीठ आवारास असणाऱ्या संरक्षक भिंतीची दुरुरती कामे करणे या कामाचे दरपत्रक सादर करणे.

महोदय,

विद्यापीठ आवारास असणाऱ्या संरक्षक भिंतीची दुरुस्ती कामे करणे या कामासाठी खाली नमूद केलेल्या अटी व शर्ती नुसार दरपत्रक मागविण्यात येत आहे.

- प्रत्यक्षात सदर कामाच्या ठिकाणी आपण पाहणी करून आपण ज्या संस्थाच्या नावाने दरपत्रक घेतले आहे त्याच संस्थेच्या लेटरहेडवर दरपत्रक भरुन सिलबंद करुन दिनांक 31/10/2020 दुपारी 1:00 वाजेपर्यंत विद्यापीठाच्या बांधकाम कक्षात सादर करावे.
- 2) विषयांकीत काम कार्यादेश मिळाल्यापासून सलग 30 दिवसांत पूर्ण केले पाहिजे.
- काम पूर्ण करण्यास विलंब झाल्यास प्रती दिन रूपये १००/- इतका विलंब आकार आकारण्यात येईल व त्याची वजावट आपणास देय असणाऱ्या रकमेतून करून उर्वरित रकमेचे देयक अदा करण्यात येईल.
- 4) वर उल्लेखलेले दर हे वाहतूक, मजुरी, तूटफूट, वेस्टेज, लोर्डिंग, अनलोर्डिंग, विद्यापीठामध्ये वस्तू पोहचविणे आवश्यक असणारे स्कॅपहोर्ल्डींग साहीत्य, इत्यादी सहीतचे भरावेत व त्यात कोणत्याही कारणास्तव वाढ देय राहणार नाही.
- संपूर्ण काम समाधानकारकरित्या पूर्ण झाल्यावर कामाचे देयक/ देयके मंजूर दरानुसार व नियमानुसार वजावटी करून विद्यापीठास सोयीरकर अशा बॅंकेच्या धनादेशाद्वारे अदा करण्यात येईल.
- 6) सदर कामासाठी दोष भरपाई कालावधी हा काम पूर्ण झाल्याच्या दिनांकापासून ६ महिने इतका असेल.
- 7) दोप भरपाई कालावधीसाठी (६ महिने) सुरक्षा अनामत ठेव म्हणून एकूण कामाच्या रक्कमेच्या पाच टक्के (५%) इतकी रक्कम वजा करण्यात येईल व सदरहू रक्कम दोष कालावधी संपल्यानंतर मा. कार्यकारी अभियंता यांच्या अहवालानुसार देण्यात येईल.
- 8) नियमानुसार लागू असणारा वस्तू व सेवा कर स्वतंत्ररीत्या अदा करण्यात येईल.

सोबतः सदर कामाचे कोरे दरपत्रक

प्रत : पुढील कार्यवाहीसाठी : १) कार्यकारी अभियंता, बांधकाम व देखभाल कक्ष 2)विद्यापीठ संकेतस्थळ

YASHWANTRAO CHAVAN MAHARASHTRA OPEN UNIVERSITY, NASHIK <u>SCHEDULE - 'B'</u> Repairing of Compound Wall at various location around the campus at

Name of work:-YCMOU,Nasik.

Sr.No.	Description of Item of work	Rate	Unit	Qty	Amount
1	Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.5 m.) By Mechanical Means		Cum	12.69	
2	Providing and laying Cast in situ/Ready Mix cement concrete in M- 10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc)		Cum	1.17	
3	Providing and laying in situ /Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. including bailing out water, Steel centering formwork, laying/pumping cover blocks, compaction and curing roughening the surface if special finish is to be provided (Excluding reinforcement and structural steel) etc. complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc)		Cum	2.16	
4	Providing and laying Cast in situ/Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal for R.C.C. columns as per detailed designs and drawing or as directed including steel centering, formwork, cover blocks, laying/pumping, compaction finishing the formed surfaces with cement mortar 1:3 of sufficient minimum thickness to give a smooth and even surface or roughening if special finish is to be provided and curing etc. complete,(Excluding reinforcement and structural steel).with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc)		Cum	0.40	
5	Providing and laying Cast in situ/Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal for R.C.C. beams and lintels as per detailed designs and drawings or as directed including steel centering, formwork, cover blocks, laying/pumping, compactionand roughening the surface if special finish is to be provided and curing etc. complete. (Excluding reinforcement and structural steel). with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc)		Cum	0.93	
6	Providing uncoursed rubble masonry of trap / granite / quartzite / gneiss stones in cement mortar 1:6 in foundation and plinth of inner walls / in plinth of external walls including bailing out water manually , striking joints on un exposed faces and watering etc.complete.		Cum	4.05	

	GST will paid separately as applicable.		ŀ	Say	
15	Concentina Coil Wire Page 527 Sr. no. 09		Rmt	60.00 Total	
14	Providing and fixing in position TMT - FE - 500 bar reinforcement of various diameters for R.C.C. pile caps, footings, foundations, slabs, beams columns, canopies, staircase, newels, chajjas, lintels pardis, copings, fins, arches etc. as per detailed designs, drawings and schedules. including cutting, bending, hooking the bars, binding with wires or tack welding and supporting as required complete.		MT	0.20	
13	Providing and erecting Y type barbed wire fencing with seven rows of wire with 2.45 mm dia G.I. pipe (Rezan/ concentiDeleted ire 0.75 mm dia) with hot dip and G.I. coated hooks as per drawing supported on M.S. angle 50 x 50 x 6 mm at 2.5 mtr. c/c including fixing and fastening with wire, painting M.S. angles with one coat of red lead primer and two coat of oil paint etc. complete.		Rmt	60.00	
12	Providing and erecting 1.5 metre high wire fencing with seven rows of barbed wire supported on M.S.Angles (50mm x 50mm x 6mm) at 2.5 Metres, Center to center including excavating pits for foundqtion, fixing post in cement cocnrete 1:4:8 of size 45 x 45 x 45 cm fastening the wire and painting the M.S.Angles with one coat of red lead primer and two coats of painting etc.complete.		Rmt	75.00	
11	Providing patti/ band 150mm wide on plastered surface 12 mm to 15 mm thick in C.M. 1:3 line and level including neat finishing scaffolding curing etc. complete.		Rmt	76.00	
10	Providing patti/ band 100mm wide on plastered surface 12 mm to 15 mm thick in C.M. 1:3 line and level including neat finishing scaffolding curing etc. complete.		Rmt	76.00	
9	Providing rough cast cement plaster externally in two coats to concrete, brick or stone masonry surfaces in all positions with base coat of 12 to 15 mm thick in C.M. 1:4 and rough cast treatment 12mm thick in proportion 1:1 1/2:3 including scaffolding and fourteen days curing complete.	:	Sqm	57.00	
8	Providing second class Burnt Brick masonry with conventional/ I.S. type bricks in cement mortar 1:6 in superstructure including striking joints, raking out joints, watering and scaffolding etc. Complete	(Cum	12.42	
7	of trap/ granite/quartzite/gneiss metal for coping to plinth or parapet, moulded or chamfered as per drawing or as directed including steel centering, plywood/ steel formwork compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.) With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc)		Cum	2.75	

Contractors Signature With Stamp